



GE
Lighting



PAR 36 4405 12.8V 24425

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



WORLDWIDE PARTNER

Product data

Cap/Base	Screw terminal
Bulb Shape	PAR
Bulb Diameter [mm]	114
Maximum Overall Length [mm]	70
Light Center Length [mm]	41.27
Net weight per piece [g]	248
Gross weight per piece [g]	250
Brand	General Electric (GE)

Performance data

Nominal beam angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	50000

Electrical data

Nominal power [W]	30
Nominal lamp voltage [V]	12
Lamp Current [A]	2.34
Coil type	C-6
Ballast Required	Yes

Logistic data

DUN Code	00043168244251
Pack Quantity	12
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special purpose lamp – Aircraft. Not suitable for household illumination.