TUNGSRAM[™]

Innovation is our heritage EST. 1896






Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas





Product data

Product Code	24673
Light Center Length [mm]	41.27
Bulb Shape	PAR
Bulb Diameter [mm]	114
Maximum Overall Length [mm]	70
Net weight per piece [g]	437
Gross weight per piece [g]	546
Brand	GE Lighting
Cap/Base	Screw terminal

Performance data

Nominal/ Rated Beam Angle [°]	15
Nominal center beam candlepower (CBCP) [cd]	55000
Rated Lumens [lm]	210
Weighted energy consumption [kWh/1000h]	31.8
Useful lumens (at 90° cone) [lm]	210
Energy efficiency class (EEC)	D

Electrical data

Rated power [W]	30.0
Lamp Current [A]	4.69
Coil type	C-6
Dimming Capability	Yes
Ballast Required	Yes
Nominal power [W]	30
Nominal lamp voltage [V]	6

Logistic data

DUN Code	00043168246736
EAN Code	0043168246736
Pack Quantity	12
Layer quantity	240 UK
Layer quantity UK	240
Pallet quantity EUR (PC)	1520
Pallet quantity UK (PC)	1200
Outer case size	310 x 209 x 218 (mm)
Product status	Phased-out

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.